

Offer inquiry form Graphite Coating Machines

O.N	Functional parameters:	Information on the fulfillment of a given functionality by entering YES or NO
1.	Coating machine with a chamber is a mobile device (on wheels)	
2.	Smooth regulation of the amount of graphite applied on the surface of the medium for 3-4-core cables	
3.	Placing such much guns in the talker's chamber is enough to cover the whole surface of the medium for 3-4-core cables	
4.	The price includes one employee training	

O.N	Technical parameter	Required values of technical parameters	Information about meeting the requirements (indicate if the value meets the condition) by entering YES OR NO	Information about meeting the requirements (enter the value of the parameter of the offered device)	Comments (enter if applicable)
1.	The range of cable diameters	from \varnothing 15mm to \varnothing 100mm	
2.	Range of production height of the device axis	from 150 cm to 180 cm	
3.	Possibility of inclination of the graphite chamber in the range of angles	from 0° to 45°	
4.	Number of applicators in the graphite chamber	Placing such much guns in the talker's chamber is enough to cover the whole surface of the medium for 3-4-core cables	
5.	Electrostatic dispenser adapted for production at speed	to 50m/min or more	
6.	The ability to regulate the amount of graphite applied to the center.	Manual or digital setting	
7.	No graphite escaping from the graphite chamber. No dusting of the environment in which the coating works.	No dusting around the coating machine.	
8.	Graphite type	Loose material	